

DATA CAPTURE SPECIFICATIONS:

RFID	
Frequency	13.56MHz ±7KHz
Reading Range	within 30mm depending on type of tags
HF RFID Reader	ISO 15693, 14443A, 14443B, 18000-3 mode-1
Barcode Scanner (2D)	
Decode Mode	1D: EAN/UPC, GS1 Databar, RSS, Code 39, Code 128, UCC/ EAN 128, ISBN, ISBT, Interleaved, Matrix, Industrial and Standard 2 of 5, Codabar, Code 93/93i, Code 11, MSI, Plessey, Telepen, postal codes (Australian Post, BPO, Canada Post, Dutch Post, Japan Post, PostNet, Sweden Post) 2D: Data Matrix, PDF417, Micro PDF 417, Codablock, Maxicode, QR, Aztec, GS1 Composite codes, Direct Part Marking Reading multicodes and barcodes on mobile phone screens available
Scan Rate	2D mode: 56 images per second, auto adaptive; Linear (1D) emulation mode: 200 images per second, auto adaptive
Scan Angle	Horizontal: 38.9°; Vertical: 25.4°
Optical Resolution	752 (H) x 480 (V) pixels, 256 gray levels
Print Contrast	Down to 30%
Versions	Standard range and high density

* Specifications subject to change without notice.

DT418SC-MD

BASIC OPERATION GUIDE

ENGLISH

INTRODUCTION

Thank you for acquiring the DT418SC-MD, part of the DT Research Medical Handheld Terminal line. The DT418SC-MD offers a 3.5" outdoor-viewable touch screen, and optional RFID and barcode scanner in a compact and lightweight package. The DT418SC-MD enables efficient point-of-service applications, inventory management, and field services. With IP54 sealed front panel, the DT418SC-MD performs well inside and outside.

The DT Research Medical Handheld Terminal provides the precise features needed to streamline operations and improve productivity, data accuracy, and service.

PACKAGE CONTENTS

1. One DT418SC-MD
2. Basic operation guide
3. Stylus lanyard and hand strap


* The actual package contents may vary depending on the configuration acquired.

PRECAUTIONS

- Always exercise care when operating and handling the DT418SC-MD.
- Do not disassemble any portion of the DT418SC-MD as this will void any product warranty on DT418SC-MD.
- Do not use any power adapter or charging cradle other than the one provided with the device or acquired from the manufacturer or its partners.
- In the unlikely event that abnormal noise, strange odor, or smoke is present, immediately power down the DT418SC-MD and disconnect all power sources. Please report the problem to your device provider immediately.



DT418SC-MD Outlook



- A** Programmable buttons
- B** Speaker
- C** Suspend/ Resume
- D** Barcode scanner
- E** Power button
- F** Scanner trigger button
- G** RFID reader
- H** Battery cover
- I** Stylus
- J** Headphone jack
- K** Mini USB port

Button Functions

- Enable/ disable soft keyboard (Programmable)
- Programmable
- System Utility
- Suspend/ Resume
- Hold +press Touch screen calibration

DT418SC-MD LED Status Indicators

1. Power Mode Status Indicator:

- Blue: Device is powered on
- Blinking Blue: Main battery charging
- Orange: Low battery mode
- Blinking Orange: Extremely low battery mode
- Off: Device is powered off or in suspend mode

2. Wi-Fi Status Indicator:

- Blue: The device has been connected to a wireless AP
- Blinking blue: The device is connecting to a wireless AP
- Off: Wi-Fi is disabled



ACCESSORIES:



AC-DC Adapter PN: ACC-410-03

Used to charge handheld battery, and pass through power for charging cradle.

Handstrap PN: AAC-010-14

Designed to let user securely grip the terminal.

USB Cable PN: ACC-410-05

For data transmission and charging device battery.

SPECIFICATIONS

System	
Processor	ARM 800 MHz
RAM	512MB
Storage	4GB Flash
Operating System	Microsoft® Windows® CE 6.0 or Windows® Mobile 6.1
Display	3.5" TFT-LCD with resistive touch; outdoor-viewable display
Display Resolution	240 x 320 (QVGA)
Network Interface	Built-in IEEE 802.11a/b/g/n WLAN, Bluetooth 2.1 with EDR
Control Switch and Buttons	1 power button, 4 front buttons, 2 trigger buttons
Indicator	1 power-on LED indicator, 1 WLAN enable/ communication indicator
Speaker	Built-in speaker
Input/Output Ports	1 mini USB (for charging and ActiveSync only), 1 headset jack
Power	
AC/DC Adapter	Input: 100 – 240V AC; Output: 5V DC, 2A
Battery Type	Li-ion battery 3760 mAh, 3.7V
Mechanical	
Enclosure	PC+ABS, TPR
Stylus	Non-electronic tip
Dimensions (H x W x D)	5.5 x 3.1 x 1.4 in/ 140 x 81.8 x 36.5 mm
Weight	0.69 lbs/ 314 g
Environmental	
Regulatory	FCC Class B, CE, C-Tick, RoHS compliant
Water and Dust Resistance	Front Panel: IP54
Temperature	Operation: 0°C - 40°C; Storage: -20°C - 60°C
Humidity	0% - 90% non-condensing

* Specifications subject to change without notice.